

LAWNMAX

CEAT
SPECIALTY

FEATURE

Higher tread depth than R-3 tires provide better traction and better life

FEATURE

Rounded shoulder design provides low soil compaction.

FEATURE

Directional tread pattern for comfortable ride and lower rate of wear

FEATURE

Lawnmax tread design ensures great self-cleaning properties.

FEATURE

Radial construction with block pattern for larger footprint, lower ground pressure.



LIST OF SIZES

SIZE	LI/SI
280/70R16	82A8/B TL
280/70R16	112A8/B TL
360/70R24	122A8/B TL

All tyres conform to ETRTO & TRA standards. Sizes available as of 02/2022.



Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm / in	mm / in	mm / in	mm / in	Speed Symbol	bar	psi	Static	10 6	20 12	30 19	40 25
280/70R16	W8, W9					112A8/B	0.8	1250	820	670	580	545	545
							12	2750	1810	1480	1280	1200	1200
		286	800	361	2388		1.2	1590	1040	850	740	690	690
		11.3	31.5	14.2	94.0		17	3500	2290	1870	1630	1520	1520
							1.6	1960	1280	1050	910	850	850
							23	4320	2820	2310	2000	1870	1870
							2.4	2580	1680	1380	1200	1120	1120
							35	5680	3700	3040	2640	2470	2470
360/70R24	W9 W10					122A8/B	0.8	2190	1430	1170	1020	950	950
							12	4820	3150	2580	2250	2090	2090
		357	1152	522	3438		1.2	2880	1880	1540	1340	1250	1250
		14.1	45.4	20.6	135.4		17	6340	4140	3390	2950	2750	2750
							1.4	3130	2040	1670	1460	1360	1360
							20	6890	4490	3680	3220	3000	3000
							1.6	3450	2250	1850	1610	1500	1500
							23	7600	4960	4070	3550	3300	3300

All tires confirms ETRTO T&RA & STRO standards

