

MULTILOADMAX

CEAT
SPECIALTY

FEATURE

Gives better stability on road

BENEFIT

Big centre block

FEATURE

Better driving comfort & self cleaning

BENEFIT

Unique angular grooves

FEATURE

Uniform load distribution and good puncture & impact resistance

BENEFIT

Steel belted carcass

FEATURE

Good traction on-road & off-road

BENEFIT

Robust block design



LIST OF SIZES

SIZE	LI/SI
250/80R16	123D/127A8
265/70R16.5	130A2/123A8
305/70R16.5	146A2/138A8
340/80R18	138D/143A8
360/70R20	131D/136A8
360/80R20	143D/147A8
360/80R24	145D/150A8
360/80R28	142D/146A8
400/70R18	143D/147A8
400/70R20	144D/149A8
400/80R24	151D/156A8
400/80R28	153D/158A8
440/80R28	158D/163A8
440/80R34	155D/159A8
480/80R34	159D/164A8
480/80R38	161D/166A8
600/70R30	166D/171A8
710/70R42	180D/185A8

All tyres conform to ETRTO & TRA standards. Sizes available as of 02/2022.



Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Speed Radius	Load Index	Infl. press.	Recommend load, kg (lbs)									
		SW	OD						Speed, km/h (mph)							Cyclic operation		
		mm	mm			constant load							10	15				
		in	in	mm	mm	(SRI)	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40	10 6	15 9	
250/ 80R16									0.8	1360	740	650	620	590	560	515	890	790
									12	3000	1630	1430	1370	1300	1230	1130	1960	1740
									1.2	1720	940	820	780	750	700	650	1120	1000
									17	3790	2070	1810	1720	1650	1540	1430	2470	2200
	W8	265	810	367	2443			123D/ 127A8	1.6	2110	1150	1010	960	920	860	800	1380	1230
	W7	10.4	31.9	14.5	96				23	4650	2530	2220	2110	2030	1890	1760	3040	2710
	W9								3.2	3040	1660	1450	1380	1320	1240	1150	1990	1770
									46	6700	3660	3190	3040	2910	2730	2530	4380	3900
									4.5	4090	2230	1950	1860	1780	1670	1550	2680	2390
									65	9010	4910	4300	4100	3920	3680	3410	5900	5260
340/ 80R18									0.8	2310	1260	1100	1050	1010	950	875	1510	1350
									12	5090	2780	2420	2310	2220	2090	1930	3330	2970
									1.6	3590	1960	1710	1630	1560	1470	1360	2350	2090
									23	7910	4320	3770	3590	3440	3240	3000	5180	4600
	DW11	343	1001	449	3019			138D/ 143A8	2.4	4750	2590	2270	2160	2070	1940	1800	3110	2770
		13.5	39.4	17.7	119				35	10460	5700	5000	4760	4560	4270	3960	6850	6100
									3.2	5150	2810	2460	2340	2240	2110	1950	3370	3000
									46	11340	6190	5420	5150	4930	4650	4300	7420	6610
									4	6230	3400	2970	2830	2710	2550	2360	4080	3630
									58	13720	7490	6540	6230	5970	5620	5200	8990	8000
360/ 70R20									0.8	2310	1260	1100	1050	1010	950	875	1510	1350
									12	5090	2780	2420	2310	2220	2090	1930	3330	2970
									1.2	3040	1660	1450	1380	1320	1240	1150	1990	1770
									17	6700	3660	3190	3040	2910	2730	2530	4380	3900
	W11	353	1030	466	3106	475		131D/ 136A8	1.6	3700	2020	1760	1680	1610	1510	1400	2420	2160
	W10	13.9	40.6	18.3	122				23	8150	4450	3880	3700	3550	3330	3080	5330	4760
	W12								2.4	4880	2660	2330	2220	2130	2000	1850	3200	2850
									35	10750	5860	5130	4890	4690	4410	4070	7050	6280
									3.2	5150	2810	2460	2340	2240	2110	1950	3370	3000
									46	11340	6190	5420	5150	4930	4650	4300	7420	6610
360/ 80R20									0.8	2640	1440	1260	1200	1150	1080	1000	1730	1540
									12	5810	3170	2780	2640	2530	2380	2200	3810	3390
									1.2	3390	1850	1620	1540	1480	1390	1285	2220	1980
									17	7470	4070	3570	3390	3260	3060	2830	4890	4360
	W11	357	1088	489	3281	500		143D/ 147A8	1.6	4090	2230	1950	1860	1780	1670	1550	2680	2390
	W10	14.1	42.8	19.3	129				23	9010	4910	4300	4100	3920	3680	3410	5900	5260
	W12								3.2	5910	3230	2820	2690	2580	2420	2240	3880	3450
									46	13020	7110	6210	5930	5680	5330	4930	8550	7600
									4	7190	3920	3430	3270	3130	2940	2725	4710	4200
									58	15840	8630	7560	7200	6890	6480	6000	10370	9250
360/ 80R24									0.8	2880	1570	1370	1310	1250	1180	1090	1890	1680
									12	6340	3460	3020	2890	2750	2600	2400	4160	3700
									1.2	3700	2020	1760	1680	1610	1510	1400	2420	2160
									17	8150	4450	3880	3700	3550	3330	3080	5330	4760
	W11	357	1189	540	3586	550		145D/ 150A8	1.6	4490	2450	2140	2040	1960	1840	1700	2940	2620
	W10	14.1	46.8	21.3	141				23	9890	5400	4710	4490	4320	4050	3740	6480	5770
	W12								3.2	6420	3500	3060	2920	2790	2620	2430	4200	3740
									46	14140	7710	6740	6430	6150	5770	5350	9250	8240
									4	7660	4180	3650	3480	3340	3130	2900	5020	4470
									58	16870	9210	8040	7670	7360	6890	6390	11060	9850

All tires confirms ETRTO T&RA & STRO standards

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Speed	Load Index	Infl. press.	Recommend load, kg (lbs)									
						Radius			Speed, km/h (mph)									
		Index	constant load							Cyclic operation								
		(SRI)	Speed	bar	Static	10	20	30	40	50	65	10	15					
Symbol	psi	kg	6	12	19	25	31	40	6	9								
360/ 80R28								0.8	3040	1660	1450	1380	1320	1240	1150	1990	1770	
								12	6700	3660	3190	3040	2910	2730	2530	4380	3900	
								1.2	3960	2160	1890	1800	1730	1620	1500	2600	2310	
								17	8720	4760	4160	3960	3810	3570	3300	5730	5090	
	W11	357	1300	595	3921	625	142D/	1.6	4750	2590	2270	2160	2070	1940	1800	3110	2770	
	W10	14.1	51.2	23.4	154		146A8	23	10460	5700	5000	4760	4560	4270	3960	6850	6100	
	W12							2.4	5600	3050	2670	2540	2440	2290	2120	3670	3260	
								35	12330	6720	5880	5590	5370	5040	4670	8080	7180	
								3.2	7000	3820	3340	3180	3050	2860	2650	4580	4080	
								46	15420	8410	7360	7000	6720	6300	5840	10090	8990	
400/ 70R18								0.8	2640	1440	1260	1200	1150	1080	1000	1730	1540	
								12	5810	3170	2780	2640	2530	2380	2200	3810	3390	
								1.2	3390	1850	1620	1540	1480	1390	1285	2220	1980	
								17	7470	4070	3570	3390	3260	3060	2830	4890	4360	
	13	404	1017	456	3067		143D/	1.6	4090	2230	1950	1860	1780	1670	1550	2680	2390	
	12	15.9	40.0	17.9	121		147A8	23	9010	4910	4300	4100	3920	3680	3410	5900	5260	
								3.2	5910	3230	2820	2690	2580	2420	2240	3880	3450	
								46	13020	7110	6210	5930	5680	5330	4930	8550	7600	
								4	7190	3920	3430	3270	3130	2940	2725	4710	4200	
								58	15840	8630	7560	7200	6890	6480	6000	10370	9250	
400/ 70R20								0.8	2720	1480	1300	1240	1180	1110	1030	1780	1590	
								12	5990	3260	2860	2730	2600	2440	2270	3920	3500	
								1.2	3480	1900	1660	1580	1520	1430	1320	2280	2030	
								17	7670	4190	3660	3480	3350	3150	2910	5020	4470	
	13	404	1068	481	3221	500	144D/	1.6	4360	2380	2080	1980	1900	1780	1650	2850	2540	
	12SDC	15.9	42.0	18.9	127		149A8	23	9600	5240	4580	4360	4190	3920	3630	6280	5590	
	14							3.2	6070	3310	2900	2760	2650	2480	2300	3980	3540	
								46	13370	7290	6390	6080	5840	5460	5070	8770	7800	
								4	7390	4030	3530	3360	3220	3020	2800	4840	4310	
								58	16280	8880	7780	7400	7090	6650	6170	10660	9490	
400/ 80R24								0.8	3390	1850	1620	1540	1480	1390	1285	2220	1980	
								12	7470	4070	3570	3390	3260	3060	2830	4890	4360	
								1.6	5280	2880	2520	2400	2300	2160	2000	3460	3080	
								23	11630	6340	5550	5290	5070	4760	4410	7620	6780	
	DW13	404	1250	565	3770		151D/	2.4	6230	3400	2970	2830	2710	2550	2360	4080	3630	
	DW12	15.9	49.2	22.2	148		156A8	35	13720	7490	6540	6230	5970	5620	5200	8990	8000	
								3.2	7390	4030	3530	3360	3220	3020	2800	4840	4310	
								46	16280	8880	7780	7400	7090	6650	6170	10660	9490	
								4	9110	4970	4350	4140	3970	3730	3450	5970	5310	
								58	20070	10950	9580	9120	8740	8220	7600	13150	11700	
400/ 80R28								0.8	3590	1960	1710	1630	1560	1470	1360	2350	2090	
								12	7910	4320	3770	3590	3440	3240	3000	5180	4600	
								1.6	5600	3050	2670	2540	2440	2290	2120	3670	3260	
								23	12330	6720	5880	5590	5370	5040	4670	8080	7180	
	DW13	404	1351	615	4075		153D/	2.4	6600	3600	3150	3000	2880	2700	2500	4330	3850	
		15.9	53.2	24.2	160		158A8	35	14540	7930	6940	6610	6340	5950	5510	9540	8480	
								3.2	8120	4430	3870	3690	3540	3320	3075	5320	4740	
								46	17890	9760	8520	8130	7800	7310	6770	11720	10440	
								4	9640	5260	4600	4380	4200	3940	3650	6310	5620	
								58	21230	11590	10130	9650	9250	8680	8040	13900	12380	

All tires confirms ETRTO T&RA & STRO standards

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Speed Radius Index (SRI)	Load Index	Infl. press.	Recommend load, kg (lbs)									
		SW	OD						Speed, km/h (mph)									
		mm	mm						constant load								Cyclic operation	
		in	in						Static	10	20	30	40	50	65	10	15	
										6	12	19	25	31	40	6	9	
440/80R28								0.8	4220	2300	2020	1920	1840	1730	1600	2770	2460	
								12	9300	5070	4450	4230	4050	3810	3520	6100	5420	
								1.2	5280	2880	2520	2400	2300	2160	2000	3460	3080	
								17	11630	6340	5550	5290	5070	4760	4410	7620	6780	
	DW14L	441	1415	641	4268			158D/	1.6	6600	3600	3150	3000	2880	2700	2500	4330	3850
	W15L	17.4	55.7	25.2	168			163A8	23	14540	7930	6940	6610	6340	5950	5510	9540	8480
									3.2	9370	5110	4470	4260	4080	3830	3550	6140	5470
									46	20640	11260	9850	9380	8990	8440	7820	13520	12050
									4	11220	6120	5360	5100	4890	4590	4250	7350	6550
									58	24710	13480	11810	11230	10770	10110	9360	16190	14430
440/80R34								0.8	4620	2520	2210	2100	2010	1890	1750	3030	2700	
								12	10180	5550	4870	4630	4430	4160	3850	6670	5950	
	DW14L	441	1568	717	4729			155D/	1.6	7190	3920	3430	3270	3130	2940	2725	4710	4200
	W15L	17.4	61.7	28.2	186			159A8	23	15840	8630	7560	7200	6890	6480	6000	10370	9250
									2.4	8320	4540	3970	3780	3620	3400	3150	5450	4850
									35	18330	10000	8740	8330	7970	7490	6940	12000	10680
									3.2	10230	5580	4880	4650	4460	4190	3875	6700	5970
									46	22530	12290	10750	10240	9820	9230	8540	14760	13150
480/80R34								0.8	5150	2810	2460	2340	2240	2110	1950	3370	3000	
								12	11340	6190	5420	5150	4930	4650	4300	7420	6610	
	DW15	479	1632	743	4922			159D/	1.6	8120	4430	3870	3690	3540	3320	3075	5320	4740
		18.9	64.3	29.3	194			164A8	23	17890	9760	8520	8130	7800	7310	6770	11720	10440
									2.4	9640	5260	4600	4380	4200	3940	3650	6310	5620
									35	21230	11590	10130	9650	9250	8680	8040	13900	12380
									3.2	11550	6300	5510	5250	5030	4730	4375	7570	6740
									46	25440	13880	12140	11560	11080	10420	9640	16670	14850
480/80R38								0.8	5440	2970	2600	2470	2370	2220	2060	3560	3170	
								12	11980	6540	5730	5440	5220	4890	4540	7840	6980	
	DW15	479	1733	794	5227			161D/	1.6	8580	4680	4100	3900	3740	3510	3250	5620	5010
		18.9	68.2	31.2	206			166A8	23	18900	10310	9030	8590	8240	7730	7160	12380	11040
									2.4	10230	5580	4880	4650	4460	4190	3875	6700	5970
									35	22530	12290	10750	10240	9820	9230	8540	14760	13150
									3.2	12210	6660	5830	5550	5320	5000	4625	8000	7120
									46	26890	14670	12840	12220	11720	11010	10190	17620	15680
600/70R30								0.8	7150	3900	2970	2830	2710	2550	2360	4080	3630	
								12	15750	8590	6540	6230	5970	5620	5200	8990	8000	
								1.2	9110	4970	3780	3600	3450	3240	3000	5190	4620	
								17	20070	10950	8330	7930	7600	7140	6610	11430	10180	
	DW20	601	1580	745	4691	625		166D/	1.6	11090	6050	4600	4380	4200	3940	3650	6310	5620
	DW18	23.7	62.2	29.3	185			171A8	23	24430	13330	10130	9650	9250	8680	8040	13900	12380
									2.4	12910	7040	5360	5100	4890	4590	4250	7350	6550
									35	28440	15510	11810	11230	10770	10110	9360	16190	14430
									3.2	16100	8780	6680	6360	6100	5720	5300	9170	8160
									46.4	35460	19340	14710	14010	13440	12600	11670	20200	17970
710/70R42								0.8	6230	3400	2970	2830	2710	2550	2360	4080	3630	
								12	13720	7490	6540	6230	5970	5620	5200	8990	8000	
								1.2	7920	4320	3780	3600	3450	3240	3000	5190	4620	
								17	17440	9520	8330	7930	7600	7140	6610	11430	10180	
	DW23	716	2050	932	6183	975		180D/	1.6	9640	5260	4600	4380	4200	3940	3650	6310	5620
	DW25	28.2	80.7	36.7	243			185A8	23	21230	11590	10130	9650	9250	8680	8040	13900	12380
									2.4	17160	9360	8190	7800	7480	7020	6500	11250	10010
									35	37800	20620	18040	17180	16480	15460	14320	24780	22050
									3.2	21120	11520	10080	9600	9200	8640	8000	13840	12320
									46.4	46520	25370	22200	21150	20260	19030	17620	30480	27140

All tires confirms ETRTO T&RA & STRO standards

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommend load, kg (lbs)													
		SW	OD					mm	mm	mm	mm	Speed, km/h (mph)									
												in	in	in	in	constant load				Cyclic operation	
																Static	10	20	25	30	40
bar	psi	6	12	16	19	25	6	9													
265/ 70R16.5	8.25	266	773	353	2331	130A2/ 123A8	0.8	1150	630	550	530	520	500	750	670						
							12	2530	1390	1210	1170	1150	1100	1650	1480						
							1.2	1500	810	710	690	680	650	980	870						
							17	3300	1780	1560	1520	1500	1430	2160	1920						
							1.6	1840	1000	870	850	830	800	1200	1070						
							23	4050	2200	1920	1870	1830	1760	2640	2360						
							3.2	2960	1610	1400	1360	1340	1285	1930	1720						
							46	6520	3550	3080	3000	2950	2830	4250	3790						
							4	3570	1900	1690	1640	1610	1550	2330	2080						
58	7860	4190	3720	3610	3550	3410	5130	4580													
305/ 70R16.5	9.75	307	831	376	2506	146A2/ 138A8	0.8	1780	970	840	820	810	775	1160	1040						
							12	3920	2140	1850	1810	1780	1710	2560	2290						
							1.2	2240	1220	1060	1030	1010	975	1460	1310						
							17	4930	2690	2330	2270	2220	2150	3220	2890						
							1.6	2710	1480	1290	1250	1230	1180	1770	1580						
							23	5970	3260	2840	2750	2710	2600	3900	3480						
							3.2	4490	2440	2130	2070	2030	1950	2930	2610						
							46	9890	5370	4690	4560	4470	4300	6450	5750						
							4	5430	3000	2570	2500	2450	2360	3540	3160						
58	11960	6610	5660	5510	5400	5200	7800	6960													

All tires confirms ETRTO T&RA & STRO standards

