

FEATURES AND BENEFITS

Extra-deep tread,
with curved tread bars

Better self cleaning &
traction in wet soil



Flatter tread

Reduces soil
compaction



Dual step tie bar

Prevents mud
clogging while adding
traction & side hill
slip resistance



Stepped lug design

Good grip in wet
& moist soil



Bolstered nose
at tread center

Improved wear &
performance



Buttressed
bar base

Better
self cleaning



*Read more about warranty policy on page 89

FARMAX R2



FARMAX R2

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	PR	Load Index Speed	Infl. press.	Recommended load, kg (lbs)	
		SW	OD						Speed, km/h (mph)	
		mm/in	mm/in	mm/in	mm/in		Symbol	bar	psi	30
20.8-38	DW18x38	530	1886	850	5750	10 PR	148A8/151A6	1.5	3450	3150
		20.9	74.3	33.5	226.4			22	7600	6940
23.1-30	DW20X30	590	1765	800	5380	10 PR	147A8/151A6	1.8	3450	3075
		23.2	69.5	31.5	211.8			26	7600	6780
14.9-28	W13	380	1406	630	4280	8 PR	126A8/130A6	1.8	1900	1700
		15.0	55.4	24.8	168.5	10 PR	130A8/134A6	2.2	2120	1900
23.1-26	DW20	590	1660	760	5060	10 PR	145A8/149A6	1.4	3250	2900
		23.2	65.4	29.9	199.2			20	7160	6390
18.4-26	DW16X26	467	1498	700	4560	10 PR	138A8/142A6	1.8	2650	2360
		18.4	59.0	27.6	179.5			26	5840	5200
14.9-24	W13	380	1310	620	3990	6 PR	119A8/123A6	1.4	1550	1360
		15.0	51.6	24.4	157.1			20	3420	3000