

ELEVETA X3

FEATURE

Alternate continuous lugs with high contact area

BENEFIT

Maximum stability and load distribution

FEATURE

Superior tread compound

BENEFIT

High resistance to wear, tear and cuts

FEATURE

Tough nylon casing

BENEFIT

High load carrying capacity with excellent durability



MACHINERY



Forklift

| Size | Type | PR | Rim | Unloaded dimension | | SLR | RC | Load Carrying Capacity | | | | | | | | | |
|-------------|------|----|------|--------------------|------|------|------|------------------------|------------|-----------|------------|-----------|-----|------|-----|------|-----|
| | | | | SW | OD | | | Infl. Press | Max. Speed | Max. Load | Max. Speed | Max. Load | | | | | |
| | | | | mm | mm | | | | | | | | bar | kmph | kg | kmph | kg |
| | | | | in | in | | | | | | | | psi | mph | lbs | mph | lbs |
| 6.50-10 NHS | TT | 12 | 5.00 | 177 | 588 | 276 | 1711 | 9 | 25 | 2145 | 25 | 1650 | | | | | |
| | | | | 7.0 | 23.1 | 10.9 | 67.4 | 131 | 15 | 4730 | 15 | 3638 | | | | | |

All tires confirms ETRTO T&RA & STRO standards