

# FARM IMPLEMENT 404



**FEATURE**

- Multi rib
- Large air chamber

**BENEFIT**

- Reduce compaction and increased flotation


**FEATURE**

- Wide tread
- High volume

**BENEFIT**

- High load carrying capacity

**MACHINERY**



Implement

| Size      | LI/SS  | PR | Type | Rim Width | Unloaded dimension |     | SLR | RC   | Load capacity |            |          |     |      |     |
|-----------|--------|----|------|-----------|--------------------|-----|-----|------|---------------|------------|----------|-----|------|-----|
|           |        |    |      |           | SW                 | OD  |     |      | Infl. Press   | Max. Speed | Max Load |     |      |     |
|           |        |    |      |           | mm                 | mm  |     |      |               |            |          | bar | kmph | kg  |
|           |        |    |      |           | in                 | in  |     |      |               |            |          | psi | mph  | lbs |
| 500/50-17 | 143 A8 | 10 | TL   | 16.00DC   | 500                | 945 | 415 | 2752 | 2             | 40         | 2725     |     |      |     |
|           |        |    |      |           | 20                 | 37  | 16  | 108  | 29            | 25         | 6010     |     |      |     |
|           | 152 A8 | 14 | TL   | 16.00DC   | 500                | 945 | 415 | 2752 | 2.8           | 40         | 3550     |     |      |     |
|           |        |    |      |           | 20                 | 37  | 16  | 108  | 41            | 25         | 7825     |     |      |     |
|           | 154 A8 | 18 | TL   | 16.00DC   | 500                | 945 | 415 | 2752 | 3.6           | 40         | 3750     |     |      |     |
|           |        |    |      |           | 20                 | 37  | 16  | 108  | 52            | 25         | 8265     |     |      |     |

All tires confirms ETRTO T&RA & STRO standards