

# LOADPRO



**FEATURE**

Greater lug overlap and more lugs in footprint

**BENEFIT**

Uniform load distribution

**FEATURE**

Extra reinforced Sidewalls

**BENEFIT**

Additional lateral stability


**FEATURE**

Strong bead

**BENEFIT**

Better carcass strength and load carrying capacity

## MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum.	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius	Speed	Static		Constant load					Cyclic operation		
		mm	mm	mm				bar	10	20	30	40	50	10	15
		in	in	in				psi	6	12	19	25	31	6	9
480/ 80R26	W15L	479	1428	636	4262		167A8/B	1.6	7340	3990	3480	3320	3190	3190	4790
						2.3		16170	8790	7670	7310	7030	46255	10550	9410
	2.2					8830		4800	4190	3990	3840	3840	5760	5150	
	3.2					19450		10570	9230	8790	8460	55680	12690	11340	
	3.2					10990		5980	5210	4970	4780	4780	7170	6410	
	4.6					24210		13170	11480	10950	10530	69310	15790	14120	
	4					12540		6810	5940	5670	5450	5450	8180	7300	
	5.8					27620		15000	13080	12490	12000	79025	18020	16080	